Underlayment Plywood

Square Edge

Tongue & Groove

Coastal produces underlayment panels as defined in US Product Standard **PS1-09** for Construction and Industrial Plywood. Underlayment plywood is specially constructed for installation in flooring applications where puncture resistance is a requirement. These panels are designed with thicker face veneer and/or limited voids in the ply beneath the face. Our 19/32 and 23/32 Performance Category thicknesses are produced with **Group 1** Southern Yellow Pine veneers and carry the **"STURD-I-FLOOR"** designation with the accompanying Span Ratings for single-layer floor construction. The glue bond classification of our Underlayment is **Exposure 1**.

We offer 19/32 and 23/32 underlayment in both Square Edge and Tongue & Groove panels. Our underlayment grades are also available in Structural-1 specifications and grademark. Please contact the sales office for special orders.

Production Item	Performance Category	#Plys	Pcs/Unit	Span Rating	Construction Layup	Notes
Underlayment	11/32 15/32	3 4	88 70		C Plugged Face D Back D Inner plies	Our BC panels are approved for Underlayment
Underlayment STURD-I-FLOOR	19/32 23/32	4 5	56 46	20oc 24oc	C Plugged face C veneer under face D Back D inner plies	Available in square edge and T & G Structural-1 is also available by special order